



High Performance Paint and Coating Systems

TECHNICAL DATA SHEET

SHIELDSEAL CT SEALER

DESCRIPTION: SHIELDSEAL CT SEALER is a Premium Quality quick drying acrylic concrete tile sealer.

RECOMMENDED USE: Formulated to penetrate and prime, non glazed concrete tiles in preparation for THERMOBOND or ROOFBOND PREMIUM FINISH coating systems.

APPLICATION PROCESS: Surface preparation is crucial and is the responsibility of the Builder/Contractor/Applicator. Weather conditions must be considered and deemed suitable before proceeding. High humidity will affect drying and recoat times.

APPLICATION DETAILS / GUIDE: Using airless spray, brush, or roller. Thinning the product is not recommended. If using airless spray, a tip size of 519 is recommended. Clean up can be done with water. The indicated film thickness when wet is 180 microns (WFT), and when dry is 45 microns (DFT). It is recommended to apply at least 1 coat, but additional coats may be required for desired coverage.

TYPICAL PROPERTIES:

Colour: Grey

Finish: Flat

Size: 15 Ltr

Volume solids: 50%

Theoretical spreading rate: 6 m² / Litre

Application surface temperature: 10°C to 40°C

Touch Dry: 30 minutes*

Recoat: 2 hours *

Full Cure: 10-14 days*

Drinking Water Safe: After 10 days* curing and initial rinse (rain or garden hose pressure). Shelf life: 24 Months

*All figures are quoted at 25° Celsius and 50% Relative Humidity



High Performance Paint and Coating Systems

TECHNICAL DATA SHEET

SHIELDSEAL CT SEALER

HEALTH AND SAFETY:

Contact The Poisons Information Center on Phone: 0800 764 766 or a doctor.

Ingestion: Do not induce vomiting. Give water to drink. Seek medical assistance.

Eye Contact: Flush eyes using eye baths until irritation subsides. Seek medical assistance.

Inhalation: Remove to fresh air. Seek medical assistance

Skin Contact: Wash thoroughly with soap and water. Launder clothing before reuse. Seek medical assistance if irritations persist.

Medical attention: Treat symptomatically.

First Aid Facilities: Eye Baths, safety showers.

RECOMMENDATIONS AND PRECAUTIONS:

Ensure that appropriate workplace health and safety methods and PPE are used when working with this product.

Ventilation: Ensure adequate ventilation when using this product.

Drinking water: When drinking water collection systems are in place, Shieldcoat recommends disconnecting the system prior to commencing work, then allowing 10 days of curing and a thorough fresh water rinse (rain or garden hose pressure) before reconnecting the system. Ensure that this product is applied in full accordance with Shieldcoat recommendations.

Care and Maintenance: Protect the coating from abrasive contact for 10 days. Wash down periodically with a mild detergent solution to refresh and preserve the coating.

MSDS: Available on request or download from the Shieldcoat website. www.shieldcoat.co.nz

DISCLAIMER: Shieldcoat advises that the applicator of this product is responsible to determine and verify its suitability for the intended use prior to application. The data and recommendations contained within this document were true and accurate at the time of writing.