Ultramax Exterior



Premium self priming acrylic for exterior walls and soffits

Product Description

Ultramax Exterior is a self-priming paint designed for exterior walls and soffits, offering superior protection against the elements. Available in white, strong, and ultra-deep bases, it provides a low sheen or satin finish that enhances the look of your exterior surfaces while resisting weathering, UV damage, and moisture. Ideal for both residential and commercial applications.

Ultramax Exterior

Directions for use

Apply as the first or second coat on clean, dry exterior walls and soffits. Use a tip size of 517 for spray application or a suitable roller for larger surfaces. Ensure surface is prepared and free of contaminants before application. Perfect for long-lasting exterior finishes.

| Surfaces | |
|----------------|--------------|
| Ceilings | |
| Interior Walls | |
| Interior Doors | |
| Exterior Doors | |
| Garage Door | |
| Trims | |
| Bricks | \checkmark |
| Barge Board | \checkmark |
| Window Frames | |
| Fence | \checkmark |
| Plaster | \checkmark |
| Weather Board | \checkmark |
| Roof | |
| Decks | |

| Attribute | |
|---------------|--------------|
| Water Based | \checkmark |
| Solvent Based | |
| Pure Acrylic | |
| UV Stable | \checkmark |
| Washable | |
| High Opacity | \checkmark |
| Anti Bleed | |
| Anti Fungal | \checkmark |

Bucket Size

| | 1L | 4L | 10L | 15L | 20L |
|---------|--------------|--------------|--------------|-----|-----|
| Plastic | | | \checkmark | | |
| Metal | \checkmark | \checkmark | | | |

| Sheen | |
|--------------|--------------|
| Matt | |
| Flat | |
| Low Sheen | \checkmark |
| Satin | \checkmark |
| Semi Gloss | |
| Gloss | \checkmark |
| Base | |
| Strong | \checkmark |
| I lltra Deen | ./ |

White

 \checkmark

| Colour | |
|----------|--------------|
| Light | \checkmark |
| Dark | \checkmark |
| Clear | \checkmark |
| Category | |



Application Brush

| Brush | \checkmark |
|--------|--------------|
| Roller | \checkmark |
| Spray | \checkmark |

| Wet Film Build | 70 Microns | Spread Rate | 14m² / ltr | Touch Dry | 30 Minutes |
|----------------|------------|-----------------|------------|-------------|-------------|
| Dry Film Build | 30 Microns | Number of Coats | 2 | Recoat Time | 120 Minutes |