Ultraseal WB

Easy sand sealer & undercoat for interior use

SHIELDCOAT High Performance Paint and Coating Systems

Product Description

Ultraseal WB is a water-based interior sealer and undercoat designed to provide a smooth, uniform surface for topcoats. It seals porous surfaces, improves adhesion, and enhances the durability of finishes. Ideal for use on drywall, plaster, and wood, Ultraseal WB offers quick drying time, low odour and easy sand formula, making it perfect for residential and commercial interiors.

Sand with 180-22g with no fill sandpaper



Directions for use

Apply as the first coat on prepared surfaces to promote adhesion and a smooth finish. Use a tip size of 517 for spray application or a suitable roller for larger areas. Allow to dry before applying the topcoat. Ideal for walls, ceilings, and trim in interior spaces.

Surfaces	
Ceilings	✓
Interior Walls	✓
Interior Doors	✓
Exterior Doors	
Garage Door	
Trims	✓
Bricks	
Barge Board	
Window Frames	✓
Fence	
Plaster	
Weather Board	
Roof	
Decks	

Attribute	
Water Based	✓
Solvent Based	
Pure Acrylic	✓
UV Stable	
Washable	
High Opacity	✓
Anti Bleed	
Anti Fungal	✓

Sheen	
Matt	
Flat	
Low Sheen	
Satin	
Semi Gloss	
Gloss	
Base	
Strong	
Ultra Deep	
White	✓

Chaan

Light	✓
Dark	
Clear	
Category	
Interior	✓
Exterior	
Application	
Brush	✓
Roller	✓
Spray	✓

Colour

			~	
ĸı	ICI	(et		176

	1L	4L	10L	15L	20L
Plastic			✓	\checkmark	\checkmark
Metal	✓	✓			

Wet Film Build	90 Microns
Dry Film Build	50 Microns

Spread Rate	12m² / Itr
Number of Coats	1+

Touch Dry	30 Minutes
Recoat Time	120 Minutes

