

Basecoat CDA

High build filler for concrete tile and decramastic roofs

SHIELD COAT
High Performance Paint and Coating Systems

Product Description

Basecoat CDA is a premium acrylic basecoat designed as a high-build filler for concrete and decramastic tiles. It provides excellent surface filling, smoothing out imperfections and ensuring a uniform surface for topcoats. Ideal for preparing concrete and decramastic tile roofs, Basecoat CDA enhances adhesion, durability, and the overall finish of subsequent coatings.



Directions for use

Apply as the first coat to prepared concrete or decramastic tile roofs. Use a tip size of 521 for spray application or a suitable roller for larger areas. Ensure the surface is clean and dry before application. Perfect for filling gaps and smoothing surfaces before topcoats.

Surfaces

Galvanized Iron	
Bitumen	
Asphalt Shingle	
Decramastic	✓
Concrete Tile	✓
TPO / Membrane	

Attribute

Water Based	✓
Solvent Based	
Pure Acrylic	✓
UV Stable	
Washable	
High Opacity	✓
Anti Bleed	
Anti Corrosive	
Anti Fungal	

Sheen

Matt	
Satin	
Gloss	

Base

Strong	✓
Ultra Deep	✓
White	

Colour

Light	✓
Dark	✓
Clear	✓

Category

Interior	
Exterior	✓

Application

Brush	✓
Roller	✓
Spray	✓
Trowel	

Bucket Size

	1L	4L	10L	15L	20L
Plastic		✓		✓	✓
Metal					

Wet Film Build	180 Microns
Dry Film Build	90 Microns

Spread Rate	5m ² / ltr
Number of Coats	2+

Touch Dry	30 Minutes
Recoat Time	120 Minutes

