

Roofbond Premium

Topcoat for all roof substrates

SHIELDCOAT

High Performance Paint and Coating Systems

Product Description

Roofbond Premium is a high-performance acrylic membrane designed as a topcoat for all roof substrates, providing superior durability and protection. Available in gloss, satin, and matt finishes, as well as strong, ultra-deep, and white shades, it enhances the appearance and longevity of roofs. Roofbond Premium resists weathering, UV rays, and moisture, making it ideal for a variety of roof materials.



Directions for use

Apply as a topcoat over a prepared, primed roof surface. Use a tip size of 521 for spray application or a suitable roller for larger areas. Ensure roof is clean, dry, and free from contaminants before applying. Ideal for roofs requiring long-lasting protection and an attractive finish.

Surfaces

Galvanized Iron	✓
Bitumen	✓
Asphalt Shingle	✓
Decramastic	✓
Concrete Tile	✓
TPO / Membrane	✓

Attribute

Water Based	✓
Solvent Based	
Pure Acrylic	✓
UV Stable	✓
Washable	✓
High Opacity	✓
Anti Bleed	
Anti Corrosive	
Anti Fungal	✓

Sheen

Matt	✓
Satin	✓
Gloss	✓

Base

Strong	✓
Ultra Deep	✓
White	✓

Colour

Light	✓
Dark	✓
Clear	✓

Category

Interior	
Exterior	✓

Application

Brush	✓
Roller	✓
Spray	✓
Trowel	

Bucket Size

	1L	4L	10L	15L	20L
Plastic		✓		✓	✓
Metal					

Wet Film Build	180 Microns
Dry Film Build	90 Microns

Spread Rate	5m ² / ltr
Number of Coats	2+

Touch Dry	30 Minutes
Recoat Time	120 Minutes

