## Rustshield Zinc Primer WB

Anti corrosive zinc primer for colorsteel roofs



## **Product Description**

Rustshield Zinc Primer WB is a premium acrylic primer formulated to provide anti-corrosive protection for Colorsteel roofs. Specifically designed for zinc-coated surfaces, it prevents rust and enhances the adhesion of topcoats. This water-based primer ensures long-lasting protection against weathering and corrosion, making it ideal for maintaining the integrity and appearance of zinc-coated roofing materials.



## Directions for use

Apply as the first coat on clean, dry, and prepared Colorsteel or zinc-coated roofs. Use a tip size of 521 for spray application or a suitable roller for larger areas. Ensure the surface is free of contaminants before applying. Ideal for protecting and preparing zinc-coated roofs for further coatings.

| Surfaces        |   |
|-----------------|---|
| Galvanized Iron | ✓ |
| Bitumen         |   |
| Asphalt Shingle |   |
| Decramastic     |   |
| Concrete Tile   |   |
| TP0 / Membrane  |   |

| Attribute      |   |
|----------------|---|
| Water Based    | ✓ |
| Solvent Based  |   |
| Pure Acrylic   | ✓ |
| UV Stable      |   |
| Washable       |   |
| High Opacity   |   |
| Anti Bleed     |   |
| Anti Corrosive | ✓ |
| Anti Fungal    | ✓ |

| Sheen      |  |
|------------|--|
| Matt       |  |
| Satin      |  |
| Gloss      |  |
| Base       |  |
| Strong     |  |
| Ultra Deep |  |
| White      |  |

| Colour      |              |
|-------------|--------------|
| Light       | ✓            |
| Dark        |              |
| Clear       |              |
| Category    |              |
| Interior    |              |
| Exterior    | ✓            |
| Application |              |
| Brush       | $\checkmark$ |
| Roller      | <b>√</b>     |
| Spray       | <b>√</b>     |
| Trowel      |              |

## **Bucket Size**

|         | 1L | 4L | 10L | 15L | 20L |
|---------|----|----|-----|-----|-----|
| Plastic |    | ✓  |     | ✓   | ✓   |
| Metal   |    |    |     |     |     |

| Wet Film Build | 165 Microns |
|----------------|-------------|
| Dry Film Build | 82 Microns  |

| Spread Rate     | 6m² / Itr |
|-----------------|-----------|
| Number of Coats | 1+        |

| Touch Dry   | 30 Minutes  |
|-------------|-------------|
| Recoat Time | 120 Minutes |

