

Product Description

Shieldseal AES is a premium acrylic sealer specifically designed for the high adhesion encapsulation of asbestos-containing surfaces. It forms a durable, protective barrier, effectively sealing asbestos fibres and preventing the release of harmful particles. Ideal for asbestos roofing, walls, and other surfaces, Shieldseal AES enhances safety while preparing the substrate for topcoats and ensuring long-lasting protection.



Directions for use

Apply as the first coat to clean, dry, and prepared asbestos surfaces. Use a tip size of 517 for spray application or a suitable roller for even coverage. Ensure the surface is free of contaminants before use. Ideal for sealing and encapsulating asbestos before applying additional coatings.

Surfaces

Galvanized Iron	
Bitumen	
Asphalt Shingle	
Decramastic	
Concrete Tile	
Asbestos	✓

Attribute

Water Based	✓
Solvent Based	
Pure Acrylic	✓
UV Stable	
Washable	
High Opacity	
Anti Bleed	
Anti Corrosive	
Anti Fungal	

Sheen

Matt	
Satin	
Gloss	

Base

Strong	
Ultra Deep	
White	

Colour

Light	✓
Dark	
Clear	

Category

Interior	✓
Exterior	✓

Application

Brush	✓
Roller	✓
Spray	✓
Trowel	

Bucket Size

	1L	4L	10L	15L	20L
Plastic	✓	✓		✓	
Metal					

Wet Film Build	200 Microns
Dry Film Build	50 Microns

Spread Rate	5m ² / ltr
Number of Coats	1+

Touch Dry	30 Minutes
Recoat Time	120 Minutes

