

Product Description

Watershield is a premium acrylic membrane designed for high-build waterproofing, ideal for use below baths, showers, and select roof applications. It provides a durable, flexible, and water-resistant layer that protects surfaces from moisture and water ingress. Perfect for areas exposed to constant water contact, Watershield ensures long-lasting protection while preventing damage to underlying surfaces.



Directions for use

Apply as the first coat to clean, dry surfaces, ensuring a smooth, waterproof barrier. Use a tip size of 525 - 527 for spray application or a suitable roller for larger areas. Allow the first coat to dry before applying additional coats for enhanced waterproofing. Ideal for wet areas and certain roof applications.

Surfaces

Galvanized Iron	✓
Bitumen	✓
Asphalt Shingle	✓
Decramastic	✓
Concrete Tile	✓
TPO / Membrane	✓

Attribute

Water Based	✓
Solvent Based	
Pure Acrylic	✓
UV Stable	
Washable	
High Opacity	✓
Anti Bleed	
Anti Corrosive	
Anti Fungal	

Sheen

Matt	
Satin	
Gloss	

Base

Strong	
Ultra Deep	
White	

Colour

Light	✓
Dark	
Clear	

Category

Interior	✓
Exterior	✓

Application

Brush	✓
Roller	✓
Spray	✓
Trowel	

Bucket Size

	1L	4L	10L	15L	20L
Plastic		✓		✓	✓
Metal					

Wet Film Build	400 Microns
Dry Film Build	248 Microns

Spread Rate	2.5m ² / ltr
Number of Coats	2+

Touch Dry	60 Minutes
Recoat Time	240 Minutes

