

Product Description

Concreshield Coloured is not your ordinary concrete sealer. This heavy-duty, xylene-based, clear or coloured topcoat is engineered to provide a lasting, vibrant finish for your concrete spaces—from garages and carports to driveways and pool areas. Unlike other coloured sealers, our formula incorporates an additional thickening agent before adding the colour, resulting in superior coverage and a longer-lasting finish. It's an ideal choice for those looking for both aesthetic appeal and functional durability.



Directions for use

Apply Concreshield Coloured as the final topcoat on clean, prepared concrete surfaces such as garages, carports, driveways, and pool areas. Use a tip size of 527 for spray application or a roller for even coverage. Stir thoroughly before use to ensure uniform color and consistency. Allow sufficient drying time between coats to achieve a vibrant, durable finish. Ideal for enhancing both the appearance and durability of concrete spaces.

Surfaces

| | |
|----------------|---|
| Foot Paths | ✓ |
| Factory Floors | ✓ |
| Garage Floors | ✓ |
| New Concrete | ✓ |
| Old Concrete | |
| Timber / Decks | |
| Steps | |

Attribute

| | |
|---------------|---|
| Water Based | |
| Solvent Based | ✓ |
| Pure Acrylic | |
| UV Stable | ✓ |
| Washable | ✓ |
| High Opacity | |
| Anti Bleed | |
| Non Slip | |
| Anti Fungal | |

Sheen

| | |
|-------|---|
| Matt | |
| Satin | |
| Gloss | ✓ |

Base

| | |
|------------|--|
| Strong | |
| Ultra Deep | |
| White | |

Colour

| | |
|-------|--|
| Light | |
| Dark | |
| Clear | |

Category

| | |
|-----------------|---|
| Trafficable | ✓ |
| Non Trafficable | |

Application

| | |
|--------|---|
| Brush | ✓ |
| Roller | ✓ |
| Spray | ✓ |

Bucket Size

| | 1L | 4L | 10L | 15L | 20L |
|---------|----|----|-----|-----|-----|
| Plastic | | ✓ | ✓ | | ✓ |
| Metal | | ✓ | ✓ | | ✓ |

| | |
|----------------|-------------|
| Wet Film Build | 200 Microns |
| Dry Film Build | 90 Microns |

| | |
|-----------------|-----------------------|
| Spread Rate | 5m ² / ltr |
| Number of Coats | 2+ |

| | |
|-------------|-------------|
| Touch Dry | 30 Minutes |
| Recoat Time | 120 Minutes |

