

## Product Description

Step Safe is a premium DIY anti-slip coating system offering lasting durability for outdoor surfaces like driveways, pool surrounds, patios, and paths. Boasting the highest P5 anti-slip rating, it eliminates the need for frequent re-coating.



## Directions for use

Prepare the surface by repairing cracks. Apply a primer as the under-coat to enhance adhesion. Follow with the Step Safe base coat for anti-slip performance, then finish with Floorshield topcoat for added protection. Use appropriate rollers or brushes for even application. Allow proper drying between coats for long-lasting, safe, and durable results.

### Surfaces

Foot Paths	✓
Factory Floors	✓
Garage Floors	✓
New Concrete	✓
Old Concrete	✓
Timber / Decks	✓
Steps	✓

### Attribute

Water Based	✓
Solvent Based	
Pure Acrylic	✓
UV Stable	✓
Washable	✓
High Opacity	✓
Anti Bleed	
Non Slip	✓
Anti Fungal	✓

### Sheen

Matt	
Satin	
Gloss	✓

### Base

Strong	✓
Ultra Deep	✓
White	✓

### Colour

Light	✓
Dark	✓
Clear	

### Category

Trafficable	✓
Non Trafficable	

### Application

Brush	✓
Roller	✓
Spray	

### Bucket Size

	1L	4L	10L	15L	20L
Plastic		✓		✓	
Metal					

Wet Film Build	300 Microns
Dry Film Build	200 Microns

Spread Rate	3-4m <sup>2</sup> / ltr
Number of Coats	2

Touch Dry	30 Minutes
Recoat Time	120 Minutes

