



TECHNICAL DATA SHEET

ULTRAFLAT CEILING WHITE

UltraFlat Ceiling White is a premium ceiling flat with excellent coverage and a crisp white tone as standard. It can also be tinted to any white base colour.

Specifically formulated with enough open time to allow for application by a combination of airless spray and back rolling by just one person.

UltraFlat Ceiling White is mould and mildew resistant, making it suitable for use in bathrooms as well as exteriors

Flat White

5, 10 and 15L

APPLICATION GUIDE

- Stir the product thoroughly before use.
- Make sure the substrate is clean and free from any contamination, such as dirt, dust, or oils.
- Avoid application when temperatures are below 7°C or above 35°C.
- UltraFlat Ceiling White can be applied using a brush, roller, or airless spray gun.

ADVANCED ADHESION
HIGH OPACITY
MOULD RESISTANT
INT/EXT USE

COVERAGE: Up to 14sqm/Lt

SOLIDS: 50%

WFT: 75um DFT:35um

TOUCH DRY: 30mins

RECOAT: 2 Hours

SHELF LIFE: 24 Months

CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.

SHIELDCOAT

INTERIOR, EXTERIOR, CONCRETE & ROOF COATINGS



SHIELDCOAT AUS
1300 135 395
info@shieldcoat.com.au
www.shieldcoat.com.au

SHIELDCOAT NZ
0800 123 900
northshore@shieldcoat.co.nz
www.shieldcoat.co.nz