

Product Description

X Series CPM is a cutting-edge waterproofing membrane featuring UV-curable and crosslinkable technology that activates with sunlight exposure for enhanced durability. With self-repairing capabilities, anti-carbonation properties, and strong adhesion to various substrates, it serves as an excellent metal roof primer. Its dirt resistance, water vapor permeability, and anti-corrosive properties offer superior protection against environmental damage.



Additional Characteristics and Benefits:

UV Stable – Can be use as a finish coat, cross links under UV conditions

Compatible with all Shieldcoat exterior grade acrylic coatings

Self Priming

Trafficable (only when overcoated with Shieldcoat Stepsafe non slip)

ACM (Asbestos) encapsulation system (only when used with Shieldseal AES)

Waterproofing Membrane

10 Year Guarantee

Directions for use

Apply as the first or second coat on clean, dry, and prepared roof surfaces. Use a tip size of 525 - 527 for spray application or a suitable roller for even coverage. Allow sufficient sunlight exposure for UV activation and cross-linking. Ideal for waterproofing, priming metal roofs, and protect-

Product Pricing

Retail	\$918.85
Trade	\$550.00

20ltr Price

Surfaces

Galvanized Iron	✓
Bitumen	✓
Asphalt Shingle	✓
Decramastic	✓
Concrete Tile	✓
TPO / Membrane	✓

Attribute

Water Based	✓
Solvent Based	
Pure Acrylic	✓
UV Stable	✓
Washable	✓
High Opacity	✓
Anti Bleed	✓
Anti Corrosive	✓
Anti Fungal	✓

Sheen

Matt	
Satin	✓
Gloss	

Base

Strong	
Ultra Deep	
White	

Colour

Light	✓
Dark	✓
Clear	

Category

Interior	
Exterior	✓

Application

Brush	✓
Roller	✓
Spray	✓
Trowel	

Bucket Size

	1L	4L	10L	15L	20L
Plastic					
Metal	✓	✓			✓

Wet Film Build	320 Microns
Dry Film Build	198 Microns

Spread Rate	2-3m ² / ltr
Number of Coats	2+

Touch Dry	60 Minutes
Recoat Time	4-6 Hours

